

## Mast Design Audit Certificate

Mast Reference Type	N425
Mast Description	120m Triangular Tubular Lattice Mast
Mast Type	Guyed
Manufacturer / Supplier	RTS

The tower has been audited to SANS specifications and approved for construction with respect to the following design parameters as detailed below:

Mast Outline GA Drawing No.	New Design - TBC
Design Specification	SANS 10160-3:2019
Basic Fundamental Wind Speed / 3-Sec Gust	40m/s
Wind Return Period	50yrs
Terrain Category	B
Site Altitude	1000m Above Mean Sea Level
Ground Datum	0m
Mast Loading	0.5m <sup>2</sup> at Apex of Mast (120m) 0.5m <sup>2</sup> at 117m above NGL
Mast Deflection	0.5 Degree
Material Grade	S355JR
Bolt Grade	Grade 8.8
Mast Width	425mm
Main Leg Members	43.5mm OD 3.0mm t Circular Hollow Section OR 38.1mm OD 3.0mm t Circular Hollow Section
Diagonal Members	12mm OD Circular Round
Horizontal Members	12mm OD Circular Round
Mast Sections	40 x 3m Sections
Bolt Quantity	9x M12 Bolts between 3m sections
Initial Guy Tension – G1, G2	3.5kN
Initial Guy Tension – G3, G4, G5, G6, G7, G8	4.4kN
Guy Wire – G1, G2	6mm 1800MPa
Guy Wire – G3, G4, G5, G6, G7, G8	8mm 1800MPa
Internal Guy Foundation Distance From Mast Centre	39.52m for G1, G2, G3 and G4
Outer Guy Foundation Distance From Mast Centre	105.52m for G5, G6, G7 and G8

This document does in no way relieve the supplier of any of their responsibilities for the structure.

Mike Adair

*Pr. Eng*

*ECSA Reg No. 20180486*